



ZL30-II:

- YTO LR6108G8 engine, more powerful and low fuel consumption.
- Whole-hydraulic steering device, operating lightly and small steering radius.
- More optional accessory working implements: Joy-stick control, Log Clamp, ROPS Frame, air conditioner for cabin.
- Whole machine has high performance and cost ratio.

ZL50D-II:

- Styer technology Wechai engine, more powerful and low fuel consumption, CUMMINS or SHANGHAI D6114 is optional.
- Power-shift gearbox and single-stage 4-element hydraulic torque converter, which can automatically adjust the output torque.
- More optional accessory working implements: Joy-stick control, Log Clamp, ROPS Frame, air conditioner for cabin.
- Whole machine has high performance and cost ratio.

Model		ZL30- II	ZL50D- II
Total weight	kg	9950	16000/16550
Bucket capacity	m ³	1.8	3/3.5
Rated load	kg	3000	5000
Movable arm lifting time	s	≤6.5	≤6.8
Three item time	s	≤12	≤11.8
Min turning radius	mm	5700	5990
Forward 1-4 gear	km/h	6.5-36	0-11.5
Reverse 1-2 gear	km/h	7.5-23	0-36
Dumping clearance	mm	3050	3050/3450
Dumping reach	mm	1150	1290/1565
Overall dimension(L x W x H)	mm	7630 x 2430 x 3200	7450/7580 x 3000 x 3400
Engine model		LR6B3-22	WD615G.220
Engine rated power	kW	88	162
Fuel tank capacity	L	140	220